



OIL CAPACITIES

Oil type range recommended for all Lofrans' models is, SAE 90 – SAE 140.

| WINDLASS MODEL | CAPACITY (Lt) |
|---|---------------|
| X1 500W / 800W, SX1 500W / 800W | 0,15 |
| X1 1000W | 0,30 |
| X2 700W | 0,15 |
| X2 1000W / 1500W, SX2 1000W / 1500W, Project 1000 | 0,30 |
| X3 1500W, SX3 1500W, Project 1500 | 0,30 |
| X3 1700W, SX3 1700W | 0,30 |
| X3.5, SX3.5 | 1,00 |
| X4, SX4, Project 2000 | 1,40 |
| X5, SX5 | 1,40 |
| Capstan T500 / T700 | 0,20 |
| Capstan T1000 / T1500 / T1700 | 0,20 |
| Capstan T2000 / T2500 | 1,00 |
| Ercole Vertical | 2,80 |
| Lion, Atlas | 0,15 |
| Dorado | 0,10 |
| Kobra | 0,50 |
| Cayman 88 | 0,50 |
| Tigres | 0,50 |
| Falkon | 1,00 |
| Titan | 2,00 |
| Ercole – Horizontal | 4,00 |
| Super Ercole | 6,00 |